### **High Cube**

With high cube containers, you gain an extra foot in height compared with general-purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in 40 ft and 45 ft sizes in steel.



High Cube 40' x 8' x 9'6"

	<u> </u>		
		S	teel
		Millimetres	Feet
	Length	12,031	39'5.6"
Internal Dimensions	Width	2,352	7'8.5"
Dimensions	Height	2,698	8'10"
Door	Width	2,340	7'8.1"
Opening	Height	2,585	8'5.8"
		Kilograms	Pounds
	Max Gross	30,480	67,200
Weight	Tare	3,980	8,755
	Max Payload	26,500	58,425
		Cube Metres	Cube Feet
Internal Capacit	у	76.3	2,694
Internal Capacit	У	/6.3	2,69



High Cube 45' x 8' x 9'6"

		Steel	
		Millimetres	Feet
Internal	Length	13,544	44'6.7"
Dimensions	Width	2,352	7'8.5"
	Height	2,698	8'10"
Door Opening	Width	2,340	7'8.1"

	Height	2,585	8'5.8"
		Kilograms	Pounds
	Max Gross	30,480	67,200
Weight	Tare	4,800	10,580
	Max Payload	25,680	
		Cube Metres	Cube Feet
Internal Capacity	Internal Capacity		3,040

# **General Purpose**

 ${\sf OOCL}$  offers 20 ft and 40 ft general-purpose containers. Manufactured from steel, they are suitable for most types of cargo.



#### General Purpose 20' x 8' x 8'6"

		Concide tal poste 20 X 0 X 0 0	
		Steel	
		Millimetres	Feet
	Length	5,898	19'4.2"
Internal Dimensions	Width	2,352	7'8.6"
	Height	2,391	7'10"
Door	Width	2,340	7'8"
Opening	Height	2,280	7'5.8"
		Kilograms	Pounds
	Max Gross	24,000 / 30,480	52,910 / 67,200
Weight	Tare	2,280 / 2,280	5,030 / 5,030
Weight	Max Payload	21,720 / 28,200	47,880 / 62,170
	•	Cube Metres	Cube Feet
Internal Capacit	ty	33.2	1,171



### General Purpose 40' x 8' x 8'6"

		Steel	
		Millimetres	Feet
	Length	12,024	39'5.7'
Internal Dimensions	Width	2,352	7'8.5'
Difficilisions	Height	2,390	7'10'
Door	Width	2,340	7'8'
Opening	Height	2,280	7'5.8'
		Kilograms	Pounds
	Max Gross	30,480	70,040
Weight	Tare	3,830	8,450
	Max Payload	26,650	58,750
		Cube Metres	<b>Cube Feet</b>
<b>Internal Capacity</b>	,	67.7	2,390

# **OOCL's Reefer Equipment**

OOCL has a fleet of over thirty thousand reefers, including 20 feet standard and 40 feet high cube reefers of the following dimensions:  $\frac{1}{2} \left( \frac{1}{2} \right) = \frac{1}{2} \left( \frac{1}{2} \right) \left( \frac{1}{2} \right)$ 

### 20 Feet Reefer Container



		Millimetres	Feet
	Length	5,455 - 6,058	17' 10.7" - 19' 10.5"
	Width	2,288 - 2,295	7' 6.0" - 7' 6.3"
Internal Dimensions	Height	2,276 - 2,292	7' 5.6" - 7' 6.2"
	Height to Load Line	2,176 - 2,192	7' 1.6" - 7' 2.3"
Deer Opening	Width	2,294	7' 6.3"
Door Opening	Height	2,264 - 2,278	7' 5.1" - 7' 5.6"
		Kilograms	Pounds

Weight	Max Gross	24,000 - 30,480	52,190 - 67,196
	Tare	2,600 - 3,190	5,732 - 7,032
	Max Payload	20,840 - 27,610	45,944 - 60,869
		Cubic Metres	Cubic Feet
Internal Capacity		28.63 - 28.76	1,011.1 - 1,015.6
Internal Capac	city to Load Line	27.38 - 27.51	966.9 - 971.5

### 40 Feet High Cube Reefer Container



		Millimetres	Feet
	Length	11,552 - 11,626	37' 10.8" - 38' 1.7"
	Width	2,282 - 2,295	7' 5.8" - 7' 6.3"
Internal Dimensions	Height	2,540 - 2,548	8' 4" - 8' 4.3"
	Height to Load Line	2,440 - 2,448	8' 0.1" - 8' 0.3"
Deer Opening	Width	2,286 - 2,294	7' 6" - 7' 6.3"
Door Opening	Height	2,558 - 2,573	8' 4.7" - 8' 5.3"
		Kilograms	Pounds
	Max Gross	30,480 - 34,000	67,196 - 74,957
Weight	Tare	4,270 - 4,760	9,413 - 10,494
	Max Payload	25,805 - 29,675	56,890 - 65,422
		Cubic Metres	Cubic Feet
Internal Capacity		67.19 - 67.73	2,372.8 - 2,391.9
Internal Capacity to Load Line		64.54 - 65.07	2,279.2 - 2,297.9

### **Open Top**

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulky cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The door header can also be swung out to make the stuffing of cargo more convenient. Manufactured from steel, open top containers come in 20 ft and 40 ft sizes.



### Open Top 20' x 8' x 8'6"

	open replacement			
		Steel	Steel	
		Millimetres	Feet	
	Length	5,897	19'4.2"	
Internal Dimensions	Width	2,352	7'8.6"	
	Height	2,348	7'8.4"	
Door	Width	2,340	7'8.1"	
Opening	Height	2,280	7'5.8"	
Roof	Length	5,674	18'7.4"	
Aperture	Width	2,232	7'3.9"	
		Kilograms	Pounds	
	Max Gross	30,480	67,196	
Weight	Tare	2,260	4,982	
	Max Payload	28,220	62,214	
		Cube Metres	Cube Feet	
<b>Internal Capacity</b>	1	32.7	1,155	
			·	



### Open Top 40' x 8' x 8'6"

· · ·			
		Steel	
		Millimetres	Feet
	Length	12,032	39'5.7"
Internal Dimensions	Width	2,352	7'8.6"
D.I.I.C.1.510115	Height	2,348	7'8.4"
Door	Width	2,340	7'8.1"
Opening	Height	2,280	7'5.8"
Roof	Length	11,798	38'8.5"
Aperture	Width	2,232	7'3.9"
		Kilograms	Pounds
Weight	Max Gross	30,480	67,196
	Tare	3,980	8,774

	Max Payload	26,500	58,422
		Cube Metres	Cube Feet
Internal Capacity		66.7	2,356



Open Top (OQ) 40'x8'x9'6"

- F		
	Steel	
	Millimetres	Feet
Length	12,032	39′5.7″
Width	2,352	7′8.6″
Height (Unfolded)	2,653	8′8.3″
Width	2,340	7'8.1"
Height	2,585	8'5.8"
Length	11,798	38'8.5"
Width	2,192	7'2.3"
	Kilograms	Pounds
Max Gross	30,480	67,197
Tare	3,910	8,620
Max Payload	26,570	58,577
	Cubic Metres	<b>Cubic Feet</b>
ity	75.1	2,652
	Width Height (Unfolded) Width Height Length Width  Max Gross Tare Max Payload	Length

### Flatracks

Flatracks are especially suited to heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery. OOCL offers collapsible and non-collapsible containers with or without walls. Manufactured from steel, flatrack containers come in 20 ft and 40 ft sizes.



Flatracks 20' x 8' x 8'6"

		Steel	
		Millimetres	Feet
Internal Dimensions	Length	5,618	18'5.2"
	Width	2,438	8'
	Height (Unfolded)	2,210	7'3"
	Height (Folded)	370	1'2.6"
		Kilograms	Pounds
Weight	Max Gross	34,000	74,957
	Tare	3,000	6,614
	Max Payload	31,000	68,343

[Note: If overall width, inclusive of packing, securing and lashing materials, does not exceed 2,438mm, the cargo will be treated as 'in-gauge' in width.]



Flatracks 40' x 8' x 8'6"

		Steel		
		Millimetres	Feet	
Internal Dimensions	Length	11,652	38'2.7"	
	Width	2,438	8'	
	Height (Unfolded)	1,955	6'5"	
	Height (Folded)	650	2'1.6"	
		Kilograms	Pounds	
Weight	Max Gross	45,000	99,208	
	Tare	5,400	11,905	
	Max Payload	39,600	87,303	

[Note: If overall width, inclusive of packing, securing and lashing materials does not exceed 2,438mm, the cargo will be treated as 'in-gauge' in width.]



Flatracks (FQ) 40'x 8'x 9'6"

		Steel	
		Millimetres	Feet
Internal Dimensions	Length	11,652	38′2.7″
	Width	2,438	8′
	Height (Unfolded)	2,264	7′5″
	Height (Folded)	650	2′1.6″
		Kilograms	Pounds
Weight	Max Gross	52,500	115,743
	Tare	5,200	11,464
	Max Payload	47,300	104,279

[Note: If overall width, inclusive of packing, securing and lashing materials, does not exceed 2,438mm, the cargo will be treated as 'in-gauge' in width.]